



SAINT-GOBAIN

hydroproof®

**ECONOMICAL, WATER-BASED
ACRYLIC WATERPROOFER -
USED WITH abe® membrane**



USES

- For waterproofing all types of stable flashings
- For waterproofing parapet walls
- Sealing of joints, laps and roofing screws on corrugated roofs and gutters.

ADVANTAGES

- **hydroproof®** is an all-in-one system
- There is no need for separate primers on porous surfaces
- **hydroproof®** has excellent weathering properties, adhesion and is tough, flexible and non-toxic
- **hydroproof®** comes in a wide range of colours

COLOURS



SURFACE PREPARATION

Ensure all surfaces are clean dry, sound and free from all laitance, fungal growth, grease, oil or loose and flaking particles.

BONDING/PRIMING

Prime porous surfaces with a neat coat of **hydroproof®**. Prime metal surfaces with **4 metal primer**.

MIXING

Stir well before use.

COVERAGE

Coverage: 2.1 l/m² full system.

APPLICATION

1st coat: (after priming): apply by brush/roller using 1 l/m². Embed **abe® membrane** into wet coat, avoiding bubbles or wrinkles.

Membrane overlaps minimum 100 mm on end laps and 75 mm on side laps.

2nd coat: once **1st coat** has dried (2 - 3 hours), apply **2nd coat** by brush/roller using 0,5 l/m² and ensure membrane is fully saturated.

3rd coat: once **2nd coat** has dried, apply **3rd coat** at different angle to **2nd coat** using 0,5 l/m².

Drying time @ 25 °C

Touch dry: 1 hour

Hard dry: 24 hours

Full cure: 7 days

CLEANING

Whilst still wet, clean equipment with water. If **hydroproof®** has dried use **abe® super brush cleaner** followed by washing with soap & water.

CAUTION

Membrane must be used. Always ensure that **hydroproof®** is applied to well drained roofs.

PROTECTION ON COMPLETION

Whilst **hydroproof®** is designed for an extended life, it is important to apply a maintenance coat of **hydroproof** every 3 to 4 years.

PACKAGING

Available in 5 liter.

IMPORTANT NOTE

This data sheet is issued as a guide to the use of the product(s) concerned. Whilst **a.b.e.**® endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot accept any liability for application – because **a.b.e.**® has no direct or continuous control over where and how **a.b.e.**® products are applied.

FURTHER INFORMATION

Where other products are to be used in conjunction with this material, the relevant technical data sheets should be consulted to determine total requirements.

a.b.e.® has a wealth of technical and practical experience built up over the years in the company's pursuit of excellence in building and construction technology.

Please consult our website for our latest datasheets.

DATE UPDATED: 25/10/2023

a.b.e.® is an ISO 9001:2015 registered company
101 Main Reef Road, Boksburg North, 1459 | Tel: +27(0)11 306 9000
www.abe.co.za