

CreteCare Polish Datasheet

February 2026

Page 1 of 2

CreteCare Polish is an easy to apply, hard wearing, protective polish for cement and concrete floors and walls, terracotta tiles, slate, terrazzo, sandstone, limestone and vinyl surfaces. **CreteCare Polish** delivers excellent black heel mark, slip and wear resistance. This is a state of the art low-ammoniated and economical wear coat. Available in Gloss and Matt.

Technical Data

Type	Acrylate polymer emulsion
Colour	Opaque in wet stage and dries clear. Available in Gloss & Matt
Working time after mixing	N/A
Application temperature (ambient)	5°C to 30°C
Substrate temperature	5°C to 30°C
UV resistance	Non-yellowing internal application
Abrasive resistance	Good wearing coat to protect sealers
Density	1kg / L
Protection during application	Don't apply to hot surfaces, block sun when applying
Safety	See MSDS

Purpose

CreteCare Polish is suitable for high traffic areas and promotes abrasion, scuff and slip resistance. **CreteCare Polish** provides an economical sacrificial layer to protect and enhance the sealer.

Uses

Specifically designed to protect sealed floor and wall surfaces, can also be used on vinyl, stone, tile and wood floors.

Colours

Dries clear and is non-yellowing.

Limitations & Precautions

Interior use only. May be slippery when wet, particularly the Gloss version.

Suitable Surfaces

CreteCare Polish is suitable for new, sealed concrete floors and walls, existing sealed floors and walls from which all previous polish applications have been removed. **CreteCare Polish** can also be used on vinyl, stone, tiles and sealed wood floors.

Weather

- Do not apply if temperatures are below 10°C or exceeds 30°C.
- Do not apply to exterior surfaces if any form of precipitation (including rain, dew, snow, or condensation, etc) is expected within 12 hours of application.

Surface Preparation

New sealed floors and walls

Ensure surface is clean, dry and clear from dirt and grease.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

CreteCare Polish Datasheet

February 2026

Page 2 of 2

Existing floors and walls

For best results remove dirt, grease, and / or polish build up with Cemcrete's CreteCare Strip&Clean according to the manufacturers instructions. Remove all Strip&Clean residue with a damp microfibre cloth and allow to dry completely. It is important that all previous polish is completely removed.

Masking

For best results, all windows, doors and adjacent surfaces (especially glass or aluminium), should be masked using painter's tape and brown paper to prevent soiling these surfaces during application. All masking material must be removed at the end of the day to avoid fraying the edges of the application, and to prevent plasticizer migration or sticky residue from the tape. Care should be taken when removing the tape to ensure no product is pulled away with it.

Mixing

Use as supplied (do not dilute). Shake well before use.

Application

Apply **CreteCare Polish** thinly and evenly, preferably with a lamb's wool or micro fibre applicator. Make sure that no bubbles or streaks exist in the newly applied film. Do not rub. Allow this coat to dry for 30 minutes and apply second and third coats if required due to substrate porosity and sheen requirements. Allow for last coat to cure for at least 12 hours. Over time **CreteCare Polish** may build up and require removing to rejuvenate the surface, before applying **CreteCare Polish** afresh; refer to Cemcrete's Strip&Clean for more information.

Coverage

Coverage is approximately 25 - 30m² per 1 litre per coat, depending on surface porosity and method of application.

Cleaning

Clean all application equipment with water.

Packaging

Available in 1 and 5 litre containers.

Storage

Store out of direct sunlight and avoid extreme temperatures. Prevent from freezing. Use within 12 months from date of purchase.

Safety Precautions

In case of contact with eyes, rinse immediately with water and seek medical advice. Wear suitable protective clothing and gloves.

Manufacturer's Warranty

Cemcrete warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to Cemcrete shall be limited to replacement of the product ex-factory. Cemcrete makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.