

Slip Resistant Additive Datasheet

February 2026

Page 1 of 1

Fine, white granules to be added to the final sealer to create a more slip-resistant surface.

Purpose

To increase the slip-resistance of sealers on floors.

Advantages

- Disperses readily and evenly throughout the sealer.
- Polymeric in nature, therefore more compatible physically with sealers eg. expansion / contraction.
- Compatible with solvent-based and water-based systems.

Limitations

- May be dirt retentive.
- May discolour the decorative coating slightly, as it creates a fine texture when used.
- Reduces light reflection on the surface.

Preparation

Prior to sealing, mix the required amount of the **Slip Resistant Additive** into the final coat of sealer. Ensure sealer is applied using a suitable roller. The coverage will depend on texture. Some settling or flotation may occur, therefore stir the mix periodically (2 minute intervals).

Application

- For maximum slip resistance, add **Slip Resistant Additive** into both the final two coats of sealer (at 18g / litre).
- For medium slip resistance, add **Slip Resistant Additive** into the final coat of sealer only.
- For minimum slip resistance, overcoat the sealer containing the **Slip Resistant Additive**, with a final coat of sealer without additive.

Limitations

- If left in some solvent-type sealers for extended periods (>4 hours), there is a tendency for swelling and sticking together of the particles. Therefore use all sealer containing **Slip Resistant Additive** immediately, and do not store; discard all unused sealer.
- As with most materials it will slowly wear, hence periodic checking of slip-resistance is advisable.
- May dull gloss retention / light reflecting properties of the sealer(s).

Coverage

Generally 18g / litre, depending on type of sealer used. Refer to the relevant sealer(s) datasheet(s) for final coverage.

Packaging

Supplied in bags of 90 grams (enough for 5 litres of sealer).

Manufacturer's Warranty

Cemcrete warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to Cemcrete shall be limited to replacement of the product ex-factory. Cemcrete makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.

Cemcrete provides a comprehensive technical service based on over 4 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.